Date/Doc revision: 25-Apr-2023

Project Name: Battery Doorbell Camera

TECHNICAL SPECIFICATIONS

• Model Name: XDC03

• Camera: 2MP

• Field of View: Horizontal: 160°, Vertical: 160°

• Video: Up to 1536P, H.264 10-15FPS

Audio: 2-way, Full DuplexNight Vision: IR up to 10ft

• LEDs: RGB Main Button, Status Indicator

Motion Sensor: PIR 110° @ 10 ft, AI Human Body Detection
Microphone: Omni-directional MIC/Sensitivity -26 +/- 1dB

• **Speaker:** Built-in Speaker 1W, 0.8ohm x1

• Main Button: Multifunctional

Case Material: PC+ABSFinish/Color: Black

Power: Type-C USB, Rechargeable Battery (See Power)

Battery: Built-in 6400mAh, non-removable
Accessory: Wall Mount - Auxiliary Doorbell

• Operating Temperature: -4° to 122°F (-20° to 50°C)

Operating Humidity (Storage): 80% Max. non-condensing

Weather Proofing: IP54

• Regulatory: FCC, IC

CONNECTIVITY

• Wi-Fi: Dual Band 2.4GHz, 802.11 a/b/g/n

• **Encryption:** WPA-AES, WPA2 AES

• **Sub-GHz:** 433 MHz

DIMENSIONS

Height: 5.43 In.Width: 1.77 In.Depth: 0.94 In.

• Weight: 6.52 oz. (without mounting plate), 7.90 oz. (with mounting plate)

POWER

• Charging: 5V2A Type-C USB, DC

• 6400mAh non-removable rechargeable battery, ≈ 3.5 months under normal conditions*

*3.5-month battery life is based on the assumption of 5 motion events in daytime, 2 motion events in nighttime, 1 remote wake-up in daytime, 1 remote wake-up in nighttime, and 5 false alarms from PIR.

